

BODYGARD

TECHNICAL DATA SHEET

COLOR	: SKY BLUE
PRODUCT WIDTH	: 1500mm width
MD TENSILE	: 95 N/15mm
CD TENSILE	: 45 N/15mm
THICKNESS	: 450-550micron
GRAMAGE	: 200 g/m ²
WATER COLUMN	: 4.0 bar
CRACK BRIDGING	: > 0,4 mm
PEELING/ADHESION	: > 0,2 N/mm ²
Sd-VALUE	: > 85 m (Water vapour transmission ratio)
TEMPERATURE RESISTANCE	: -35°C -- +90°C
UV RESISTANCE	: < 500 hours
PACKAGING	: 1 ROLL
ROLL LENGTH	: 30 OR 50 METERS
SHELF LIFE	: Protect and retain from direct sun light and frosting on open weather conditions. Must be kept under dry conditions. Unopened dry kept material lifetime is approximately 24 month

FELIKS DIS TICARET LTD STI
EOSB 26 CAD NO 9
26110 ESKISEHIR
TURKEY

BODYGARD 200
WATER PROOFING MEMBRANE
ETAG 022-2: CATEGORY II

CRACK BRIDGING CAPABILITY

CATEGORY 3: 1,5mm

TENSILE AND ADHESION CAPABILITY

CATEGORY 2 : > 0.3MPa

BRIDGING CAPABILITY

CATEGORY 2: water barrier

WATER BARRIER/WATER PROOFING

CATEGORY 2: water barrier

BODYGARD 200

New Generation waterproofing membrane based on nonwovens.

The information contained in this document is based on available scientific and practical data and may vary according to the location and purpose of use of the product. FELIX is only obliged to ensure the quality of the product promised in the prescribed standard conditions. FELIX Limited Liability Company shall not be held liable for any misuse or improper use of FELIX. When this document is revised, the old editions will be invalid.